

SUBJECT**Exhaust Brake for Duramax, 6.6 Liter Isuzu****MODEL NUMBER****C20066, C20066 ST, C40066, C40067, C40068, C40069
Topkick/Kodiak 4500/5500 Not Affected**

ISUZU has made changes to the 2004 model year trucks equipped with Duramax 6.6 Liter engine.

Due to the addition of a VGT turbocharger and an EGR valve, Pacbrake has been delayed in releasing an exhaust brake for the 2004 model year engine. These brakes are now validated and available.

It is important to identify the engine by it's VIN to establish which exhaust brake is correct for the application.

Before installing an exhaust brake on a vehicle built after December 31st, 2003 please check the vehicles VIN. The 8th digit in the VIN is the engine identification and will be either a number 1 or 2 or the letter D.

From the chart below, select the correct brake noting the choices between fixed orifice or the increased retarding of the PRXB.

8TH DIGIT OF VEHICLE VIN	TYPE OF EXHAUST BRAKE	APPLICATION INFORMATION	ORDER PACBRAKE KIT NUMBER
1	Fixed Orifice Direct Mount	Vehicles with automatic transmission and optional 2nd alternator only, corner brace mounted air compressor.	C20066
1	Fixed Orifice Direct Mount	Vehicles with automatic or manual transmission without optional 2nd alternator, engine mounted air compressor.	C20066ST
1	PRXB Inline Mount	Vehicles with automatic transmission and optional 2nd alternator only, corner brace mounted air compressor.	C40066
1	PRXB Inline Mount	Vehicles with automatic or manual transmission without optional 2nd alternator, engine mounted air compressor.	C40067
2 or D	PRXB Inline Mount	Vehicles with automatic transmission and optional 2nd alternator only, corner brace mounted air compressor.	C40068
2or D	PRXB Inline Mount	Vehicles with automatic or manual transmission without optional 2nd alternator, engine mounted air compressor.	C40069

NOTE: Engine mounted air compressor is the preferred kit, corner brace mounted air compressors could produce an audible noise when pumping.

Contact **Pacbrake** Service at **1 800 663 0096**